



ⓑ NOTES:

- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
- INSULATORS: PBT GF UL 94 V-0, BLACK
- FRAME: STEEL; NICKEL PLATED
- FLOAT MOUNTS: COPPER ALLOY; NICKEL PLATED
- RIVETED INSERTS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
- COLLARS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
- CONNECTOR WILL BE SUPPLIED WITHOUT CONTACTS
- CONNECTOR IS PART MARKED: DSS2XSXXB01X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		dim. in mm	scale: 2:1	
				date			material: SEE NOTES	
				drawn	02.08.2005	Lehmenkühler	title: <b>D-SUB FEMALE</b> 15pos. CRIMP STYLE with frame and float mount	
				appd.	02.08.2005	Mickenbecker		
3 x c	Ä5047	16.01.14	Lehm.	d-old				
1 x b	Ä2880	04.12.07	Lehm.				dwg no:	DIN-A3
a	Original						16K1A1473	sh: 1
rev.	description	date	name			part no: DSS2XSXXB01X		