

# Female test connector - TPS 3/20/5 - 3246586

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Female test connector, for 4 mm test plugs, for screwing into the bridge shaft, color: silver



### Why buy this product

If All test sockets are screwed into the bridge shaft



# Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 046356 625371
GTIN	4046356625371

## Technical data

#### General

Number of positions	1
Color	silver
Material	silver-plated brass
Flammability rating according to UL 94	V0

### Dimensions

Width	5 mm
Length	5 mm
Height	20 mm
Diameter	5 mm

#### General

Ambient temperature (operation)	-40 °C 80 °C	

## Standards and Regulations

Flowershilts ration according to 11, 04	V0
Flammability rating according to UL 94	VU




# Female test connector - TPS 3/20/5 - 3246586


# Technical data

## **Environmental Product Compliance**

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

# Drawings





Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200 http://www.phoenixcontact.com